

# ACTION ATV CF500 QUAD BIKE



Available In Other Colours

## CF500

<b>Certificate :</b>	EEC, EPA, DOT	
<b>Engine</b>		
<b>Engine Type :</b>	Single Cylinder, 4-Valves, 4 Stroke	
<b>Engine Displacement :</b>	493 CC	
<b>Bore &amp; Stroke :</b>	87.5 X 82 mm	
<b>Compression Ratio :</b>	10.2 : 1	
<b>Fuel System :</b>	Carburetor	Others
<b>Max. Power Output :</b>	24 KW / 6500 rr / min	LCD Dashboard : Optional
<b>Max. Torque :</b>	38.8KW / 5500 r / min	2WD & 4WD Switch : Standard
<b>Cooling System:</b>	Water Cooled	Differential Lock : Standard
<b>Ignition :</b>	CDI	
<b>Starter :</b>	Electric & Recoil Start	
<b>Transmission :</b>	CVT	
<b>Lubrication :</b>	Pressure & Splash	
<b>Dimensions</b>		
<b>L x W x H :</b>	2320 X 1170 X 1230 mm	
<b>Wheelbase :</b>	1490 mm	
<b>Seat Height :</b>	500 mm (From Footrest)	
<b>Geound Clearance :</b>	275 mm	
<b>Fuel Capacity :</b>	19 Litres	
<b>Dry Weight :</b>	340 kg	
<b>Wheels, Suspension and Brakes</b>		
<b>Wheels Front :</b>	12 x 6.0 AT Cast Light Alloy, Spoke Steel	
<b>Wheels Rear :</b>	12 x 7.5 AT Cast Light Alloy, Spoke Steel	
<b>Tyres Front :</b>	185 / 88 -12 25 x 8 -12 40L 4PR 40kPa Tubeless	
<b>Tyres Rear :</b>	270 / 60-12 25 x 10 -12 50L 4PR 40kPa Tubeless	
<b>Suspension Front :</b>	Double Wishbone Independent Suspension, Coil Spring Oil Damp Shock Absorber	
<b>Suspension Rear :</b>	Double Wishbone Independent Suspension, Coil Spring Oil Damp Shock Absorber	
<b>Brakes Front :</b>	Hydraulic Braking, Double Disc 220 X 3.5 mm with Felly Brakes	
<b>Brakes Rear :</b>	Hydraulic Braking, Single 150 x 7.5 mm, Centralized Rakes	

# ACTION ATV X6 QUAD BIKE



## X6

### Engine

<b>Engine Type :</b>	Liquid Cooled, Single Cylinder, 4 Values, 4 Strokes
<b>Engine Displacement :</b>	594 CC
<b>Bore &amp; Stroke:</b>	96 x 82
<b>Compression Ratio :</b>	10 : 1
<b>Fuel System :</b>	Electronic Fuel Injection
<b>Max. Power Output :</b>	28 KW / 6300 rpm
<b>Max. Torque:</b>	46.9 N.m / 5500 rpm
<b>Cooling System :</b>	Liquid Cooled
<b>Ignition :</b>	Computer - Controlled Digital Transistorised with Electronic Advance
<b>Starter :</b>	Electric
<b>Transmission :</b>	CVT
<b>Lubrication :</b>	Wet Sump

### Dimensions

<b>L x W x H :</b>	2300 x 1180 x 1230 mm
<b>Track :</b>	Front: 940 mm    Rear: 860 mm
<b>Wheelbase :</b>	1490 mm
<b>Seat Height :</b>	910 mm
<b>Ground Clearance :</b>	275 mm
<b>Fuel Capacity :</b>	19 Litres (Including 3.5 litre reserve)
<b>Dry Weight :</b>	358 kg

### Wheels, Suspension and Brakes

<b>Wheels Front :</b>	12 x 6.0 AT - Spoke Cast Aluminium
<b>Wheels Rear :</b>	12 x 7.5 AT - Spoke Cast Aluminium
<b>Tyres Front :</b>	AT 25 x 8 - 12 38J Tubeless
<b>Tyres Rear :</b>	AT 25 x 8 - 12 38J Tubeless
<b>Suspension Front :</b>	Double Wishbone Independent Suspension, Nitrogen Gas Absorber
<b>Suspension Rear :</b>	Double Wishbone Independent Suspension, Nitrogen Gas Absorber
<b>Brakes Front :</b>	Hydraulic Brake, 220 x 3.5 mm

## ACTION ATV Z6 DUNE BUGGY



### Z6

<b>Certificate :</b>	EEC, EPA, DOT
<b>Engine</b>	
<b>Engine Type :</b>	Liquid Cooled, Single Cylinder, 4 Values, 4 Stroke
<b>Engine Displacement :</b>	594 CC
<b>Bore &amp; Stroke :</b>	96 X 82 mm
<b>Compression Ratio :</b>	10 : 1
<b>Fuel System :</b>	Electronic Fuel Injection
<b>Max. Power Output :</b>	28 KW / 6300 rpm
<b>Max. Torque :</b>	46.9 N.m / 5500 rpm
<b>Cooling System :</b>	Water Cooled
<b>Ignition :</b>	CDI
<b>Starting :</b>	Electric
<b>Transmission :</b>	CVT
<b>Lubrication :</b>	Pressure & Splash
<b>Dimensions</b>	
<b>L x W x H :</b>	2630 X 1320 X 1800 mm
<b>Wheelbase :</b>	1960 mm
<b>Seat Height :</b>	350 mm (From Footrest)
<b>Ground Clearance :</b>	240 mm
<b>Fuel Capacity :</b>	2.7 Litres
<b>Dry Weight :</b>	450 kg
<b>Wheels, Suspension and Brakes</b>	
<b>Wheels Front :</b>	12 x 6.0 AT - Spoke Light Alloy
<b>Wheels Rear :</b>	12 x 7.5 AT - Spoke Light Alloy
<b>Tyres Front :</b>	185 / 80 - 12 25 x 8 12 77J 4PR 40 kPa Tubeless
<b>Tyres Rear :</b>	185 / 80 - 12 25 x 10 12 77J 4PR 40 kPa Tubeless
<b>Suspension Front :</b>	Double Wishbone Independent Suspension, Coil Spring Oil Damp Shock Absorber
<b>Suspension Rear :</b>	Double Wishbone Independent Suspension, Coil Spring Oil Damp Shock Absorber
<b>Brakes Front :</b>	Hydraulic Brake, Left & Right Brake Disc. Disc dimension 220 x 4 mm x 2
<b>Brakes Rear :</b>	Hydraulic Brake, Left & Right Brake Disc. Disc dimension 220 x 4 mm x 3
<b>Others Tank Lock Key :</b>	Standard