

ACTION ATV CF500 QUAD BIKE



Available In Other Colours

CF500

Certificate :	EEC, EPA, DOT	
Engine		
Engine Type :	Single Cylinder, 4-Valves, 4 Stroke	
Engine Displacement :	493 CC	
Bore & Stroke :	87.5 X 82 mm	
Compression Ratio :	10.2 : 1	
Fuel System :	Carburetor	Others
Max. Power Output :	24 KW / 6500 rr / min	LCD Dashboard : Optional
Max. Torque :	38.8KW / 5500 r / min	2WD & 4WD Switch : Standard
Cooling System:	Water Cooled	Differential Lock : Standard
Ignition :	CDI	
Starter :	Electric & Recoil Start	
Transmission :	CVT	
Lubrication :	Pressure & Splash	
Dimensions		
L x W x H :	2320 X 1170 X 1230 mm	
Wheelbase :	1490 mm	
Seat Height :	500 mm (From Footrest)	
Geound Clearance :	275 mm	
Fuel Capacity :	19 Litres	
Dry Weight :	340 kg	
Wheels, Suspension and Brakes		
Wheels Front :	12 x 6.0 AT Cast Light Alloy, Spoke Steel	
Wheels Rear :	12 x 7.5 AT Cast Light Alloy, Spoke Steel	
Tyres Front :	185 / 88 -12 25 x 8 -12 40L 4PR 40kPa Tubeless	
Tyres Rear :	270 / 60-12 25 x 10 -12 50L 4PR 40kPa Tubeless	
Suspension Front :	Double Wishbone Independent Suspension, Coil Spring Oil Damp Shock Absorber	
Suspension Rear :	Double Wishbone Independent Suspension, Coil Spring Oil Damp Shock Absorber	
Brakes Front :	Hydraulic Braking, Double Disc 220 X 3.5 mm with Felly Brakes	
Brakes Rear :	Hydraulic Braking, Single 150 x 7.5 mm, Centralized Rakes	

ACTION ATV X6 QUAD BIKE



X6

Engine

Engine Type :	Liquid Cooled, Single Cylinder, 4 Values, 4 Strokes
Engine Displacement :	594 CC
Bore & Stroke:	96 x 82
Compression Ratio :	10 : 1
Fuel System :	Electronic Fuel Injection
Max. Power Output :	28 KW / 6300 rpm
Max. Torque:	46.9 N.m / 5500 rpm
Cooling System :	Liquid Cooled
Ignition :	Computer - Controlled Digital Transistorised with Electronic Advance
Starter :	Electric
Transmission :	CVT
Lubrication :	Wet Sump

Dimensions

L x W x H :	2300 x 1180 x 1230 mm
Track :	Front: 940 mm Rear: 860 mm
Wheelbase :	1490 mm
Seat Height :	910 mm
Ground Clearance :	275 mm
Fuel Capacity :	19 Litres (Including 3.5 litre reserve)
Dry Weight :	358 kg

Wheels, Suspension and Brakes

Wheels Front :	12 x 6.0 AT - Spoke Cast Aluminium
Wheels Rear :	12 x 7.5 AT - Spoke Cast Aluminium
Tyres Front :	AT 25 x 8 - 12 38J Tubeless
Tyres Rear :	AT 25 x 8 - 12 38J Tubeless
Suspension Front :	Double Wishbone Independent Suspension, Nitrogen Gas Absorber
Suspension Rear :	Double Wishbone Independent Suspension, Nitrogen Gas Absorber
Brakes Front :	Hydraulic Brake, 220 x 3.5 mm

ACTION ATV Z6 DUNE BUGGY



Z6

Certificate :	EEC, EPA, DOT
Engine	
Engine Type :	Liquid Cooled, Single Cylinder, 4 Values, 4 Stroke
Engine Displacement :	594 CC
Bore & Stroke :	96 X 82 mm
Compression Ratio :	10 : 1
Fuel System :	Electronic Fuel Injection
Max. Power Output :	28 KW / 6300 rpm
Max. Torque :	46.9 N.m / 5500 rpm
Cooling System :	Water Cooled
Ignition :	CDI
Starting :	Electric
Transmission :	CVT
Lubrication :	Pressure & Splash
Dimensions	
L x W x H :	2630 X 1320 X 1800 mm
Wheelbase :	1960 mm
Seat Height :	350 mm (From Footrest)
Ground Clearance :	240 mm
Fuel Capacity :	2.7 Litres
Dry Weight :	450 kg
Wheels, Suspension and Brakes	
Wheels Front :	12 x 6.0 AT - Spoke Light Alloy
Wheels Rear :	12 x 7.5 AT - Spoke Light Alloy
Tyres Front :	185 / 80 - 12 25 x 8 12 77J 4PR 40 kPa Tubeless
Tyres Rear :	185 / 80 - 12 25 x 10 12 77J 4PR 40 kPa Tubeless
Suspension Front :	Double Wishbone Independent Suspension, Coil Spring Oil Damp Shock Absorber
Suspension Rear :	Double Wishbone Independent Suspension, Coil Spring Oil Damp Shock Absorber
Brakes Front :	Hydraulic Brake, Left & Right Brake Disc. Disc dimension 220 x 4 mm x 2
Brakes Rear :	Hydraulic Brake, Left & Right Brake Disc. Disc dimension 220 x 4 mm x 3
Others Tank Lock Key :	Standard